

# SACRIFICIAL

# GRAFFITI GARD®

A Genuine  TEX•COTE® Product



## Application

Simply clean surface prior to applying clear, water based SACRIFICIAL GRAFFITI GUARD®. Apply with a roller or commercial grade spray equipment onto previously painted or uncoated substrate.

## Removal

Hot water blast all surfaces which have graffiti using 180-190 degree hot water at 800-900 P.S.I. Pressure. For small or unaccessible areas, TEXCOTE® Graffiti Stripper can be utilized. Reapply SACRIFICIAL GRAFFITI GUARD®.

## Uses

SACRIFICIAL GRAFFITI GUARD® offers excellent GRAFFITI CONTROL protection for simple walls to factories and apartment or office buildings. SACRIFICIAL GRAFFITI GUARD® preserves highway structures, sound barrier walls, civic or municipal facilities, murals, schools, mass transit and shopping malls.



**TEX•COTE®**  
TEXTURED COATINGS OF AMERICA, INC.

**Corporate Headquarters**

**& Eastern Manufacturing Facility**

2422 E. 15th Street, Panama City FL 32405-6348

Phone: 800-454-0340

Fax: 850-913-8619

Email: info@texcote.com

[www.texcote.com](http://www.texcote.com)

**Ft. Lauderdale Sales Office**

& all Dept. of Transportation (DOT) inquiries

4101 Ravenswood Road, Suite 218

Ft. Lauderdale, FL 33312-5371

Tel: 954-581-0771

Fax: 954-581-9516

**West Coast Manufacturing Facility**

5950 S. Avalon Boulevard

Los Angeles, CA 90003-1384

Tel: 323-233-3111

Fax: 323-232-1071

TEX•COTE® and GRAFFITI GARD® are registered trademarks of Textured Coatings of America, Inc. ©Copyright 2008 Textured Coatings of America, Inc. All Rights Reserved.

All TEX•COTE products comply with federal and state Volatile Organic Compound (VOC) rules and regulations, please contact your nearest TCA office for assistance on local VOC compliances in the area of intended use.