



TC400W
9/27/2005

M A T E R I A L S A F E T Y D A T A S H E E T

PRODUCT NAME: Tex•Cote 400
PRODUCT CODE: TC400W

HMIS CODES: H F R P
1*0 0 J

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: Textured Coatings of America
Corporate & East Plant Address: 2422 East 15th Street, Panama City, FL 32405
West Coast Plant: 5950 S. Avalon Blvd. Los Angeles, CA 90003

EMERGENCY PHONE : 800-424-9300 DATE PRINTED : 9/27/2005
INFORMATION PHONE : 850-769-0347 NAME OF PREPARER : Akiko Lovan

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	WEIGHT PERCENT
CRYSTALLINE SILICA QUARTZ OSHA PEL: 5 MG/M3, ACGIH TLV: 5 MG/M3	14808-60-7	10
Perlite OSHA PEL: 5 MG/M3, ACGIH TLV: 5 MG/M3	93763-70-3	4-9
Titanium dioxide OSHA PEL: 15MG/M3, ACGIH TLV: 10MG/M3, OTHER: DUST	13463-67-7	5 - 10
TRIMETHYL PENTANEDIOL MONOISOBUTYRATE OSHA PEL: N.E., ACGIH TLV: N.E.	25265-77-4	<5
* ETHYLENE GLYCOL OSHA PEL: 50PPM, ACGIH TLV: 50PPM	107-21-1	0 - 3

* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: 212 deg F SPECIFIC GRAVITY (H2O=1): 1.32
VAPOR DENSITY: HEAVIER THAN AIR EVAPORATION RATE: SLOWER THAN ETHER
COATING V.O.C.: .80 lb/gallon MATERIAL V.O.C.: 0.61 lb/gallon
SOLUBILITY IN WATER: Non Soluble
APPEARANCE AND ODOR: Fruity odor. Clear, light yellow liquid.

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT: N/A METHOD USED: SETA
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: .6 UPPER: 15.3

EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG, OTHER

SPECIAL FIREFIGHTING PROCEDURES

Respiratory equipment should be worn to avoid inhalation of concentrated vapors. Water should not be used except as fog to keep nearby containers cool.

UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers may explode when exposed to extreme heat. Cool with water spray.

===== SECTION V - REACTIVITY DATA =====

STABILITY: STABLE

CONDITIONS TO AVOID: Open flames, fire, enclosed spaces.

INCOMPATIBILITY (MATERIALS TO AVOID)

Alkaline materials, strong acids and oxidizing materials.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

Carbon monoxide, carbon dioxide, oxides of nitrogen, and possibly acrolein.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

===== SECTION VI - HEALTH HAZARD DATA =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Inhalation: Dizziness, breathing difficulty, headaches & loss of coordination.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Eye contact: Severe irritation, tearing, redness and blurred vision.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Skin contact: Can dry and defat skin causing cracks, irritation, and dermatitis.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Ingestion: Can cause gastrointestinal irritation, vomiting, nausea, and diarrhea.

HEALTH HAZARDS (ACUTE AND CHRONIC)

Inhalation-Dizziness, breathing difficulty, headaches, & loss of coordination.

Eye contact-Severe irritation, tearing, redness, and blurred vision. Skin

contact-Can dry and defat skin causing cracks, irritation, and dermatitis.

Ingestion-Can cause gastrointestinal irritation, vomiting, nausea, & diarrhea.

No chronic health effects.

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: Yes OSHA REGULATED: No

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Anesthesia, respiratory tract irritation, dermatitis, nausea, vomiting

EMERGENCY AND FIRST AID PROCEDURES

Inhalation overexposure-Move person to fresh air. If breathing stops, apply artificial respiration and seek immediate medical attention. Eye contact-flush with large quantities of water for 15 minutes. Skin contact-Wash thoroughly **with soap and water and see a doctor.** In the case of ingestion and if medical care will be delayed several hours, use three to four 1-oz shots of 86 proof whiskey for a source of ethyl alcohol before or during transport.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Eliminate ignition sources, provide good ventilation, dike spill area and add absorbent earth or sawdust to spilled liquid. Thoroughly wet w/ water and mix.

WASTE DISPOSAL METHOD

Collect absorbent/water/spilled liquid mixture into metal containers and add enough water to cover. Consult local, state & federal hazardous waste regulation before disposing into approved hazardous waste landfills. Obey relevant laws.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Use non-sparking utensils when handling this material. Avoid hot metal surface. Use in cool, well-ventilated areas. Keep containers closed when not in use. Keep away from excessive heat and open flames.

OTHER PRECAUTIONS

Smoking in area where this material is used should be strictly prohibited. Tools used with this material should be made from aluminum, brass or copper. Plastic utensils should not be used.

===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION

When spraying this material use a NIOSH approved cartridge respirator or gas mask suitable to keep airborne mists and vapor concentrations below the time weighted threshold limit values. When using in poorly ventilated and confined spaces, use a fresh-air supplying respirator or a self-contained breathing apparatus.

VENTILATION

General mechanical ventilation or local exhaust should be suitable to keep vapor concentrations below TLV. Ventilation equipment must be explosion proof.

PROTECTIVE GLOVES

Impermeable chemical handling gloves for skin protection.

EYE PROTECTION

Use chemical safety glasses, goggles, and face shields for eye protection.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Use impermeable aprons and protective clothing whenever possible to prevent skin contact. The use of head caps whenever possible is strongly recommended.

WORK/HYGIENIC PRACTICES

Eye washes and safety showers in the workplace are recommended.

===== SECTION IX - DISCLAIMER =====

To the best of our knowledge, the information contained herein is accurate, obtained from sources believed by Textured Coatings of America, Inc. to be accurate.