



TEX·COTE®

TEXTURED COATINGS OF AMERICA, INC.

PR664-28J
9/13/2005

M A T E R I A L S A F E T Y D A T A S H E E T

PRODUCT NAME: SUPERCOTE TEXTURED PRIMER CT WATERBASE HMIS CODES: H F R P
PRODUCT CODE: PR664-28J 1*0 0 J

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: Textured Coatings of America
ADDRESS : 2422 East 15th Street
Panama City, FL 32405
EMERGENCY PHONE: 800-424-9300 DATE PRINTED : 9/13/2005
INFORMATION PHONE: 850-769-0347 NAME OF PREPARER : Akiko Lovan

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	WEIGHT PERCENT
Perlite OSHA PEL: 5 MG/M3, ACGIH TLV: 5 MG/M3	93763-70-3	5
TRIMETHYL PENTANEDIOL MONOISOBUTYRATE OSHA PEL: N.E., ACGIH TLV: N.E.	25265-77-4	5
* ETHYLENE GLYCOL OSHA PEL: 50PPM, ACGIH TLV: 50PPM	107-21-1	4
Prossed Mineral Fiber OSHA PEL: 15 MG/M3, ACGIH TLV: 10 MG/M3	65996-69-2	2.28
MICA OSHA PEL: 3 MG/M3, ACGIH TLV: 3 MG/M3	012001-262	
CRYSTALLINE SILICA QUARTZ OSHA PEL: 5 MG/M3, ACGIH TLV: 5 MG/M3.21	14808-60-7	.63

* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.
N/A

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: 0 deg F - 471 deg F SPECIFIC GRAVITY (H2O=1): 1.23516
VAPOR DENSITY: LIGHTER THAN AIR EVAPORATION RATE: SLOWER THAN ETHER
COATING V.O.C.: 1.33 lb/gl MATERIAL V.O.C.: 0.85 lb/gl
SOLUBILITY IN WATER: Soluble
APPEARANCE AND ODOR: Liquid,mildly sweet odor

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT: 0 deg F METHOD USED:
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 0 UPPER: 15.3
EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG
SPECIAL FIREFIGHTING PROCEDURES
Firefighters should wear positive-pressure, self-contained breathing apparatus.
Dried product will burn.

UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers may explode when exposed to extreme heat. Cool with water spray.

===== SECTION V - REACTIVITY DATA =====

STABILITY: STABLE

CONDITIONS TO AVOID

N/A

INCOMPATIBILITY (MATERIALS TO AVOID)

Avoid strong acids, alkalies, and oxidizers.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

Carbon monoxide and carbon dioxide.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

===== SECTION VI - HEALTH HAZARD DATA =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Excessive inhalation of vapors can cause nasal and respiratory irritation.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

EYE: May cause pain. May cause slight transient (temporary) irritation with slight transient corneal injury. Vapors may irritate eyes. SKIN: Prolonged or repeated exposure may cause skin irritation leading to drying and flaking.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Single prolonged skin exposure is not likely to result in absorption of harmful amounts. Irritation and dermatitis may be accentuated by liquid becoming trapped against the skin by contaminated clothing/shoes and skin absorption may occur.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Can cause gastrointestinal irritation, nausea, vomiting, and diarrhea.

HEALTH HAZARDS (ACUTE AND CHRONIC)

ACUTE: Dizziness, nausea, light headedness, headaches, loss of coordination and equilibrium, unconsciousness, possible CNS damage and even death in confined or poorly ventilated areas. CHRONIC: Long term unprotected exposure may cause permanent brain and nervous system damage, silicosis, teratogenic effects and possible liver abnormalities, kidney damage and CNS effects.

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: Yes OSHA REGULATED: Yes Contains free silica which is a suspected carcinogen under IARC. WARNING: THIS PRODUCT CONTAINS MATERIAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER IN LABORATORY ANIMALS (CALIFORNIA PROP 65)

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Liver abnormalities, kidney damage, and central nervous system disorders. Delayed/chronic lung disorders from inhalation

EMERGENCY AND FIRST AID PROCEDURES

In the case of ingestion and if medical care will be delayed several hours, use three to four 1-oz shots of 86 proof whiskey for a source of ethyl alcohol before or during transport.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Small leaks: Mop up, wipe up, or soak up immediately. Remove to out-of-doors.
Large spills: Evacuate area, contain liquid, transfer to closeable metal containers. Keep out of water supplies.

WASTE DISPOSAL METHOD

Do not dump into sewer, on the ground, or into any body of water. Any disposal practice must be in compliance with federal, state and local laws and regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Follow protective controls set forth in Section VIII when handling this product.

OTHER PRECAUTIONS

Do not use in confined spaces such as tanks or pits without following proper entry procedures such as ASTM D-4276. Vapors may displace oxygen in confined conditions. Do not cut and weld on empty or full drums. Do not reuse drum without recycling or reconditioning in accordance with any applicable federal, state or local law.

===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION

Atmosphere levels should be maintained below the exposure guideline. When respiratory protection is required for certain operations use a NIOSH/MSHA approved air-purifying respirator. For emergency and other condition where the exposure guideline may be exceeded, use an approved positive pressure selfcontained breathing apparatus.

VENTILATION

Control airborne concentrations below the exposure guidelines. Local exhaust ventilation may be necessary for some operations. Lethal concentrations may exist in areas with poor ventilation.

PROTECTIVE GLOVES

Wear solvent resistant gloves such as viton, neoprene, butyl nitrile or equivalent to prevent skin contact.

EYE PROTECTION

Wear safety glasses. Contact lenses should not be worn. Use chemical goggle and/or face shields for possible splashing.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Solvent-resistant boots, apron, headgear and/or faceshield should be worn where splashing is possible.

WORK/HYGIENIC PRACTICES

Avoid contact with skin and avoid breathing vapors. Do not eat, drink, or smoke in work area. Wash hands before eating.

===== SECTION IX - DISCLAIMER =====

NOTICE: THE INFORMATION HEREIN IS PRESENTED IN GOOD FAITH AND BELIEVED TO BE

ACCURATE AS OF THE EFFECTIVE DATE SHOWN ABOVE. HOWEVER, NO WARRANTY, EXPRESS OR IMPLIED IS GIVEN. REGULATORY REQUIREMENTS ARE SUBJECT TO CHANGE AND MAY DIFFER FROM ONE LOCATION TO ANOTHER. IT IS THE BUYERS RESPONSIBILITY TO COMPLY WITH FEDERAL STATE OR LOCAL LAWS.