



RS500
5/20/2007

M A T E R I A L S A F E T Y D A T A S H E E T

PRODUCT NAME: RAINSTOPPER 500 (CARB)
PRODUCT CODE: RS500

HMIS CODES: H F R P
2*3 0 J

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: Textured Coatings of America
Corporate & East Plant Address: 2422 East 15th Street, Panama City, FL 32405
West Coast Plant: 5150 S. Avalon Blvd. Los Angeles, CA 90003
EMERGENCY PHONE : 800-424-9300 DATE PRINTED : 5/20/2007
INFORMATION PHONE : 850-769-0347 NAME OF PREPARER : James Essig

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	WEIGHT PERCENT
Mineral spirits OSHA PEL: 100ppm, ACGIH TLV: 100ppm	8032-32-4	15
* Acetone OSHA PEL: 750PPM, ACGIH TLV: 750PPM, OTHER: 1000STEL	67-64-1	7
CRYSTALLINE SILICA QUARTZ OSHA PEL: 5 MG/M3, ACGIH TLV: 5 MG/M3	14808-60-7	<5
Titanium dioxide OSHA PEL: 15MG/M3, ACGIH TLV: 10MG/M3, OTHER: DUST	13463-67-7	0-15
MICA OSHA PEL: 3 MG/M3, ACGIH TLV: 3 MG/M3	012001-262	<5
Magnesium Silicate Hydrate OSHA PEL:None ACGIH TLV 2MG/M3	14807-96-6	3-8
Flux Calc. Diatomaceous Earth OSHA PEL: 0.75 MG/M3	68855-54-9	<5

* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: 133 deg F - 354 deg F SPECIFIC GRAVITY (H2O=1): 1.31
VAPOR DENSITY: LIGHTER THAN AIR EVAPORATION RATE: SLOWER THAN ETHER
COATING V.O.C.: 1.71 lb/gallon MATERIAL V.O.C.: 1.48 lb/gallon
SOLUBILITY IN WATER: NO
APPEARANCE AND ODOR: Solvent odor. Pigmented liquid.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Breathing difficulties, pre-existing upper respiratory and lung disease such as bronchitis, emphysema and asthma.

EMERGENCY AND FIRST AID PROCEDURES

Inhalation: Remove to fresh air. Restore breathing. Treat asymptotically, consult a physician. Splash (EYES) Flush immediately with large amounts of water for at least 15 minutes. Take to a physician. SPLASH (SKIN): Remove contaminated clothing. Wash affected areas with soap and water. Consult a physician if irritation persists. INGESTION: Drink 2 glasses of water to dilute. Do not induce vomiting. Consult a physician or poison control center immediately. Treat symptomatically.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Small leaks: Mop up, wipe up or soak up immediately. Remove to out of doors.
Large spills: Evacuate area, contain liquid, transfer to closable metal containers. Keep out of water supplies.

WASTE DISPOSAL METHOD

Do not dump into sewers, on the ground, or into any body of water. Any disposal practice must be in compliance with state, local and federal regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Follow protective controls set forth in Section VIII when handling this product. Prevent water or moist air from entering the containers. Aluminum equipment should not be used for storage and/or transfer. Use in cool, well-ventilated areas. Keep containers closed when not in use. Keep away from excessive heat and open flames. Use non-sparking utensils when handling this material. Avoid hot metal surface.

OTHER PRECAUTIONS

Vapors are heavier than air and will collect in low areas, displacing oxygen. Do not enter confined areas such as tanks or pits without following proper entry procedures. Do not cut or weld on empty or full drums. Do not use reuse drum without recycling or reconditioning in accordance with any state, local or federal law.

===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION

When spraying this material use a NIOSH approved cartridge respirator or gas mask suitable to keep airborne mists and vapor concentrations below the time weighted threshold limit values. When using in poorly ventilated and confined spaces, use a fresh-air supplying respirator or a self-contained breathing apparatus.

VENTILATION

General mechanical ventilation or local exhaust should be suitable to keep vapor concentrations below TLV. Ventilation equip. must be explosion proof.

PROTECTIVE GLOVES: Impermeable chemical handling gloves for skin protection.

EYE PROTECTION

Use chemical safety glasses, goggles, and faceshields for eye protection.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Use impermeable aprons and protective clothing whenever possible to prevent skin contact. The use of head caps whenever possible is strongly recommended.

WORK/HYGIENIC PRACTICES

Eye washes and safety showers in the workplace are recommended. Do not eat, drink or smoke in work area. Wash hands before eating.

===== SECTION IX - DISCLAIMER =====

To the best of our knowledge, the information contained herein is accurate, obtained from sources believed by Textured Coatings of America, Inc. to be accurate. It is the buyer's responsibility to comply with federal, state, or local laws.