



Anti Graffiti Coating Systems

GRAFFITI GARD® PASTE CLEANER

DESCRIPTION

GRAFFITI GARD® Paste Cleaner is a special blend of solvents and emulsifiers used to clean graffiti off surfaces that have been protected with TEX·COTE® GRAFFITI GARD® IIIS or GRAFFITI GARD® IIIW. The cleaner takes off the graffiti,

leaving the GRAFFITI GARD® film intact to continue protecting against graffiti.

FEATURES

- Proprietary blend of solvents and emulsifiers
- Convenient paste consistency

RECOMMENDED OVER

Use on GRAFFITI GARD® IIIS or IIIW systems for cleaning of graffiti.

BENEFITS

- Cleans graffiti off permanent anti-graffiti systems

APPLICATION

Surface Use

Use to clean GRAFFITI GARD® IIIS or GRAFFITI GARD® IIIW on exterior protected surfaces. May be used for interior surfaces if area is properly ventilated.

Application Rates

Quantity of cleaner needed will depend on the amount of graffiti to be cleaned. One gallon will usually clean approximately 100 square feet of affected area.

Recommended Equipment

Cleaner may be applied by brush. Use of a soft bristled brush is recom-

mended for hard to clean areas.

Working Times

The cleaner should be allowed to sit on graffiti for 3 to 10 minutes prior to rubbing with soft bristle brush.

Removal of Graffiti - TEX·COTE® Graffiti Gard® IIIS Paste Cleaner

1. Using roller or brush, coat graffiti areas with TEX·COTE® GRAFFITI GARD® Paste Cleaner.
2. Allow to stand three (3) and not longer than ten (10) minutes.
3. Scrub with soft bristle brush. NOTE: Second application of cleaner may be needed.

4. Rinse with water and scrub if necessary with soft bristle brush. Over rough surfaces, use high pressure water. Rinse well to prevent streaking.
5. Second application may be necessary to remove graffiti.

NOTE: Early removal of graffiti is easy. Prolonged exposure requires more effort to remove. Residue from run off when cleaning the walls from graffiti should be collected and disposed according to local, State & Federal regulations.

FOR BEST PERFORMANCE

1. Do not apply over frozen or damp surfaces, or when rain or fog are present and temperature is dropping below 45°F. Avoid freezing product.
2. Air temperature for application shall be 45°F and rising.
3. Do not allow smoking in the area where paste cleaner is being used.
4. Remove graffiti as soon as possible for ease of removal.

TECHNICAL DATA

<u>Physical Property</u>	<u>Result</u>
Solvent	Blend of aromatic and aliphatic solvents
Viscosity, KU	120 Typical
Weight/gallon (pounds)	8.35 Typical
Flash Point degrees F	35 (T.C.C.)

ORDER INFORMATION

Container Size

One (1) or five (5) gallon containers.

Application Rates

Quantity of cleaner needed will depend on the amount of graffiti to be cleaned. One gallon will usually clean approximately 100 square feet of affected area.

Shelf Life

Six (6) months based on the following: containers shall be stored upright and air tight in a dry place at a temperature of 45°F to 100°F. Avoid freezing.

SAFETY

Warning

GRAFFITI GARD® Paste Cleaner contains solvents and is flammable. GRAFFITI GARD® Paste Cleaner has a flash point of 35°F. Be sure to keep all forms of ignition out of the area when in use and maintain plenty of ventilation. Use protective clothes, glasses, gloves and mask.*

*Refer to the material safety data sheet for detailed information.

First Aid

Rinse immediately with water on contact. Volatile fumes are harmful if inhaled, use in well-ventilated areas. Avoid open flames.

A respirator such as 1482-C102 (H.S.C. Corporation) or equal is recommended. Should comply with OSHA Regulations 29CFR1910134.

VOC COMPLIANCE

All TEX·COTE® products comply with federal and state Volatile Organic Compound (VOC) rules and regulations. Please contact your nearest TCA office for assistance on the local VOC compliance in the area of intended use.

WARRANTY

Upon completion of application of coating in accordance with the manufacturer's recommendations, Textured Coatings of America, Inc. will extend its limited commercial warranty for product replacement as a result of defect in the material. The manufacturer must be notified prior to the application of the coating and the application must be in compliance with the manufacturer's recommendations for installation. Textured Coatings of America, Inc. shall have no obligation to contribute to or otherwise participate in labor or cost associated with effecting repairs. Specimen copy of material warranty available upon request.



TEX·COTE®
GRAFFITI GARD®
PASTE CLEANER



TEX·COTE®
TEXTURED COATINGS OF AMERICA, INC.

CORPORATE OFFICES & EASTERN PLANT
2422 East 15th Street Panama City, Florida 32405
Tel: (850) 769-0347 Fax: (850) 913-8619

COMMERCIAL SALES OFFICE
4101 Ravenswood Road, Suite 210,
FT. Lauderdale, Florida 33312
Tel: (954) 581-0771 Fax: (954) 581-9516

WESTERN PLANT
5950 S. Avalon Blvd.
Los Angeles, California 90003
Tel: (323) 233-3111 Fax: (323) 232-1071