

UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers may explode when exposed to extreme heat. Cool with water spray.

===== SECTION V - REACTIVITY DATA =====

STABILITY: STABLE

CONDITIONS TO AVOID

Avoid open flames, welding arcs, and high temperatures.

INCOMPATIBILITY (MATERIALS TO AVOID)

Avoid strong acids, alkalies, and oxidizers.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

Carbon monoxide and carbon dioxide.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

===== SECTION VI - HEALTH HAZARD DATA =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Excessive inhalation of vapors can cause nasal and respiratory irritation

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

EYE: May cause pain. May cause slight transient (temporary) irritation with slight transient corneal injury. Vapors may irritate eyes. SKIN: Prolonged repeated exposure may cause skin irritation leading to drying and flaking

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Single prolonged skin exposure is not likely to result in absorption of high amounts. Irritation and dermatitis may be accentuated by liquid becoming trapped against the skin by contaminated clothing/shoes, and skin absorption may occur.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Swallowing this material may result in irritation of the mouth and GI tract and other effects as listed above for inhalation.

HEALTH HAZARDS (ACUTE AND CHRONIC)

ACUTE: This material is primarily a CNS depressant. May cause irritation respiratory system, dizziness, nausea, light headedness, headaches, loss coordination and equilibrium, unconsciousness, possible CNS damage and even death in confined or poorly ventilated areas. CHRONIC: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage.

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULAT: No

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Breathing difficulties

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: Remove to fresh air. Restore breathing. Treat symptomatically; consult a physician. SPLASH (EYES): Flush immediately with large amounts of water for at least 15 minutes. Take to a physician. SPLASH (SKIN): Wash affected areas with soap and water. Remove contaminated clothing. Consult a physician if irritation persists. INGESTION: drink two glasses of water to dilute. Do induce vomiting. Consult a physician or poison control center immediately. Treat symptomatically.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Small leaks: Mop up, wipe up, or soak up immediately. Remove to out-of-doors.
Large spills: Evacuate area, contain liquid, transfer to closable metal containers. Keep out of water supplies.

WASTE DISPOSAL METHOD

Do not dump into sewers, on the ground, or into any body of water. Any disposal practice must be in compliance with federal, state, and local laws and regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Follow protective controls set forth in Section VIII when handling this product.

OTHER PRECAUTIONS

Vapors are heavier than air and will collect in low areas displacing oxygen. Do not enter confined spaces such as tanks or pits without following proper procedures such as ASTM D-4276. Do not cut or weld on empty or full drums. Do not reuse drum without recycling or reconditioning in accordance with any applicable federal, state or local law.

===== SECTION VIII - CONTROL MEASURES =====
RESPIRATORY PROTECTION

Atmosphere levels should be maintained below the exposure guideline. When respiratory protection is required for certain operations use a NIOSH/MSHA approved air-purifying respirator. For emergency and other condition where the exposure guideline may be exceeded, use an approved positive pressure self-contained breathing apparatus.

VENTILATION

Control airborne concentrations below the exposure guidelines. Local exhaust ventilation may be necessary for some operations. Lethal concentrations may exist in areas with poor ventilations.

PROTECTIVE GLOVES

Wear solvent resistant gloves such as viton, neoprene, butyl nitrile or equivalent to prevent skin contact.

EYE PROTECTION

Wear safety glasses. Contact lenses should not be worn. Use chemical goggles and/or face shields for possible splashing.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Solvent-resistant boots, apron, headgear and/or faceshield should be worn if splashing is possible.

WORK/HYGIENIC PRACTICES

Avoid contact with skin and avoid breathing vapors. Do not eat, drink, or smoke in work area. Wash hands before eating.

===== SECTION IX - DISCLAIMER =====

To the best of our knowledge, the information contained herein is accurate, obtained from sources believed by Textured Coatings of America, Inc. to be accurate. HOWEVER, NO WARRANTY, EXPRESS OR IMPLIED IS GIVEN. REGULATORY REQUIREMENTS ARE SUBJECT TO CHANGE AND MAY DIFFER FROM ONE LOCATION TO ANOTHER. IT IS THE BUYER'S RESPONSIBILITY TO COMPLY WITH FEDERAL, STATE OR LOCAL LAWS.