



Anti Graffiti Coating Systems

SACRIFICIAL GRAFFITI GARD® STRIPPER

DESCRIPTION

This mild solvent stripper is a special blend of solvents and emulsifiers that are used to clean graffiti off surfaces that have been protected with TEX·COTE® SACRIFICIAL GRAFFITI GARD®. The cleaner takes off the graffiti, as well as the

sacrificial coating. After the wall has dried, SACRIFICIAL GRAFFITI GARD® may be reapplied.

FEATURES

Proprietary blend of solvents and emulsifiers

BENEFITS

- Cleans graffiti off SACRIFICIAL GRAFFITI GARD®
- Useful in small spaces where high temperature pressure wash is not practical

RECOMMENDED OVER

Used for cleaning surfaces protected with SACRIFICIAL GRAFFITI GARD®, where hot water blasting is not a practical removal technique.

APPLICATION

Surface Use

Use to clean graffiti off SACRIFICIAL GRAFFITI GARD® protected surfaces. May be used for areas where hot water blasting is not practical.

Working Time

The cleaner should be applied to the defaced SACRIFICIAL GRAFFITI GARD® and wiped off immediately. Must be wiped clean with clear water.

Application Rates

Quantity of cleaner needed will depend on the amount of graffiti to be cleaned. One gallon will usually clean approximately 200 square feet of

affected area.

Removal of Graffiti - TEX·COTE® SACRIFICIAL GRAFFITI GARD®

1. Using roller, brush or cloth, coat graffiti areas with TEX·COTE® SACRIFICIAL GRAFFITI GARD® Stripper.
2. Immediately wipe off with cloth.
3. Rinse with water and scrub if necessary with soft bristle brush. Rinse well to prevent streaking.
4. Reapply SACRIFICIAL GRAFFITI GARD® immediately.

NOTE: Residue from run off when cleaning the walls with SACRIFICIAL

GRAFFITI GARD® Stripper should be collected and disposed according to local, State & Federal regulations.

FOR BEST PERFORMANCE

1. Do not apply over frozen, damp surfaces, or when rain or fog is present. Do not apply if temperature is dropping below 45°F. Avoid

- freezing product.
2. Air temperature for application shall be 35°F and rising.
3. Do not allow smoking in the area

where SACRIFICIAL GRAFFITI GARD® Stripper is being used.

TECHNICAL DATA

Physical Property	Result
Solvent	Blend of aromatic and aliphatic solvents
Viscosity, KU, 77°F	120 Typical
Weight/gallon (pound)	7.8 Typical
Flash Point degrees F	35 (T.C.C.)

ORDER INFORMATION

Order Information

Available in one (1) or five (5) gallon containers.

Application Rates

Quantity of cleaner needed will depend on the amount of graffiti to be cleaned. One gallon will usually clean approximately 200 square feet of affected area.

Shelf Life

Shelf life is one year based on the following conditions: containers shall be stored upright and air tight in a dry place, at a temperature of 45°F to 100°F. Avoid freezing.

SAFETY

Warning

SACRIFICIAL GRAFFITI GARD® Stripper contains solvents and is flammable. SACRIFICIAL GRAFFITI GARD® Stripper has a flash point of 35°F. Be sure to keep all forms of ignition out of the area when in use and maintain plenty of ventilation. Use protective clothes, glasses, gloves and mask.* Rinse immediately with water on contact. Volatile fumes are harmful if inhaled, use in well-ventilated areas. Avoid open flames.

*A respirator such as 1482-C102 (H.S.C. Corporation) or equal is recommended. Should comply with OSHA Regulations 29CFR1910.134. Refer to the material safety data sheet for detailed information.

*Refer to the material safety data sheet for detailed information.

First Aid

Rinse immediately with water on contact. Volatile fumes are harmful if inhaled, use in well-ventilated areas. Avoid open flames.

VOC COMPLIANCE

All TEX·COTE® products comply with federal and state Volatile Organic Compound (VOC) rules and regulations. Please contact your nearest TCA office for assistance on the local VOC compliance in the area of intended use.

WARRANTY

Upon completion of application of coating in accordance with the manufacturer's recommendations, Textured Coatings of America, Inc. will extend its limited commercial warranty for product replacement as a result of defect in the material. The manufacturer must be notified prior to the application of the coating and the application must be in compliance with the manufacturer's recommendations for installation. Textured Coatings of America, Inc. shall have no obligation to contribute to or otherwise participate in labor or cost associated with effecting repairs. Specimen copy of material warranty available upon request.



TEX·COTE®
SACRIFICIAL GRAFFITI
GARD® STRIPPER



TEX·COTE®
TEXTURED COATINGS OF AMERICA, INC.

CORPORATE OFFICES & EASTERN PLANT

2422 East 15th Street Panama City, Florida 32405
Tel: (850) 769-0347 Fax: (850) 913-8619

COMMERCIAL SALES OFFICE

4101 Ravenswood Road, Suite 218,
FT. Lauderdale, Florida 33312
Tel: (954) 581-0771 Fax: (954) 581-9516

WESTERN PLANT

5950 S. Avalon Blvd.
Los Angeles, California 90003
Tel: (323) 233-3111 Fax: (323) 232-1071