



MATERIAL SAFETY DATA SHEET

PRODUCT NAME: XL 70 W PRIMER
 PRODUCT CODE: PR70W

Page 1 of 4

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY
--

MANUFACTURER'S NAME / ADDRESS

TEXTURED COATINGS OF AMERICA, INC.

Corporate Offices & Eastern plant
 2422 EAST 15TH ST.
 PANAMA CITY, FL 32405
Info- (850) 769-0347

TRADE NAME: XL 70W PRIMER

MAIN USE: MULTI-PURPOSE PRIMER

Western Plant
 5950 SOUTH AVALON BLVD.
 LOS ANGELES, CA 90003
Info- (323) 233-3111
(800) 424-9300 (CHEMTREC)

INITIAL ISSUE DATE: JANUARY 12, 2007

REVISION DATE:

PREPARED BY: J.W.ESSIG

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS
--

INGREDIENTS	Wt. %	CAS Number
GROUND LIMESTONE	15-40	001317-65-3
TITANIUM DIOXIDE	5-15	013463-67-7
ZINC OXIDE	1-5	001314-13-2
DIATOMACIOUS EARTH	1-5	068855-54-9
TRIMETHYL PENTANEDIOL MONOISOBUTYRATE	1-5	025265-77-4
PROPYLENE GLYCOL	1-5	000057-55-6

EXPOSURE LIMITS (ppm)

INGREDIENTS (CAS)	OSHA		ACGIH		OTHER (SEE NOTE 1)
	TWA	STEL	TWA	STEL	
001317-65-3	5mg/m ³	ND	2mg/m ³	ND	Respirable Dust
013463-67-7	10mg/m ³	ND	10mg/m ³	ND	Total Dust
001314-13-2	5mg/m ³	ND	5mg/m ³	10mg/m ³	Respirable Dust
068855-54-9	NE	NE	NE	NE	
025265-77-4	NE	NE	NE	NE	
000057-55-6	NE	NE	NE	NE	

LEGEND: (M) MAX. EXPOSURE LIMIT; (S) OCCUPATIONAL EXP. LIMIT; (R) SUPPLIERS REC. LIMIT, (+) PERCUTANEOUS RISK
 NOTE 1: VALUES MEANINGFUL ONLY WHEN HARDENED PRODUCT IS ABRADED, GROUND, ETC.

COATING VOC: 99 grams/liter

MATERIAL VOC: 41 grams/liter

SECTION 3: HAZARDS IDENTIFICATION
--

EMERGENCY OVERVIEW

FORM: LIQUID
 COLOR: WHITE
 ODOR: MILD

WARNING STATEMENTS

MAY CAUSE EYE IRRITATION
 MAY CAUSE SKIN IRRITATION
 MAY CAUSE RESPIRATORY TRACT IRRITATION

PRIMARY ROUTES OF ENTRY: INHALATION, SKIN ABSORPTION, EYE CONTACT.

HEALTH HAZARDS (ACUTE AND CHRONIC EXPOSURES)

EYES: ACUTE – NO SPECIFIC DATA. MAY CAUSE IRRITATION REDNESS, PAIN & TEARING.

CHRONIC – MAY CAUSE CLOUDING OF CORNEA WITH REPEATED CONTACT.

SKIN CONTACT: ACUTE – TRANSIENT IRRITATION, REDNESS AND DISCOMFORT.

CHRONIC – REPEATED OR PROLONGED CONTACT MAY CAUSE ALLERGIC REACTION.



MATERIAL SAFETY DATA SHEET

PRODUCT NAME: XL 70 W PRIMER
PRODUCT CODE: PR70W

Page 2 of 4

SECTION 3: HAZARDS IDENTIFICATION CON'T.

SKIN ABSORPTION: ACUTE – NO SPECIFIC DATA.

CHRONIC – COMPONENTS MAY CAUSE IRRITATION.

INHALATION: ACUTE – NO SPECIFIC DATA. MAY CAUSE IRRITATION OF RESPIRATORY TRACT, HEADACHE AND DIZZINESS.

CHRONIC – PROLONGED EXPOSURE MAY CAUSE IRRITATION OF RESPIRATORY TRACT, HEADACHE AND DIZZINESS..

INGESTION: ACUTE – NO SPECIFIC DATA. COMPONENTS HAVE LOW ORDER OF TOXICITY.

CHRONIC – NO SPECIFIC DATA.

CONDITIONS AGGRAVATED BY EXPOSURE: SKIN DISORDERS AND ALLERGIES.

CARCINOGENIC DATA: THIS PRODUCT CONTAINS NO CARCINOGENS IN CONCENTRATIONS OF 0.1% OR GREATER.

TERATOGENICITY: ND

MUTAGENICITY: ND

EMBRYOTOXICITY: ND

SYNERGISTIC MATERIAL: ND

OVEREXPOSURE EFFECTS: LACRIMATION OF EYES, SKIN IRRITATION, DIZZINESS.

IRRITANCY: YES

SENSITIZER: NO

SECTION 4: FIRST AID MEASURES

GENERAL: REMOVE PERSON FROM AFFECTED AREA AND MAKE COMFORTABLE. TREAT SYMPTOMATICALLY.

EYES: FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL ATTENTION.

SKIN: REMOVE PRODUCT AND FLUSH AFFECTED AREA WITH WATER FOR 15 MINUTES. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION.

INHALATION: MOVE TO FRESH AIR. GIVE ASSISTED RESPIRATION IF BREATHING HAS STOPPED OR IS LABORED (CALL A PHYSICIAN).

INGESTION: GIVE 3 – 4 GLASSES OF WATER OR MILK IF PERSON CONSCIOUS. **DO NOT INDUCE**

VOMITING! OBTAIN MEDICAL CARE AND TREATMENT. NO MORE THAN SLIGHTLY TOXIC IF SWALLOWED.

SECTION 5: FIRE FIGHTING MEASURES

FLASH POINT: >100⁰ C (212⁰ F)

CONDITIONS OF FLAMMABILITY: NA

FLAMMABLE LIMITS: LEL: NA UEL: NA

AUTO IGNITION TEMP.: NA

HAZARDOUS COMBUSTION PRODUCTS: CARBON MONOXIDE, CARBON DIOXIDE

SENSITIVITY TO IMPACT: NONE

SENSITIVITY TO STATIC DISCHARGE: NONE

EXTINGUISHNG MEDIA: WATER SPRAY, CO2, DRY CHEMICAL

SPECIAL FIRE FIGHTING PROCEDURES: NONE LIKELY WITH SMALL QUANTITIES. FOR LARGE QUANTITIES, FIREFIGHTERS AND OTHERS EXPOSED TO VAPORS OR PRODUCTS OF COMBUSTION SHOULD WEAR BUTYL RUBBER BOOTS, GLOVES AND BODY SUIT. SELF-CONTANED BREATHING APPARATUS SHOULD BE WORN.

UNUSUAL FIRE AND EXPLOSIVE HAZARDS: NONE KNOWN.

SECTION 6: ACCIDENTAL RELEASE MEASURES

PERSONAL PROTECTION: REFER TO SECTION 8.

ENVIRONMENTAL PRECAUTIONS: PREVENT PRODUCT ENTERING SOIL, NATURAL WATERS AND DRAINS.

METHODS FOR CLEANING AND TAKING UP: LARGE SPILLAGES SHOULD BE CONTAINED AND PUMPED INTO A RECEIVING VESSEL. SMALL SPILLAGES SHOULD BE ABSORBED ON INERT ABSORBANT. FOR DISPOSAL METHODS REFER TO SECTION 13.



MATERIAL SAFETY DATA SHEET

PRODUCT NAME: XL 70 W PRIMER
PRODUCT CODE: PR70W

Page 3 of 4

SECTION 7: HANDLING AND STORAGE

GENERAL: KEEP AWAY FROM HEAT OR FLAME. STORE AND HANDLE IN WELL VENTILATED AREAS. KEEP COOL, DRY AND IN CLOSED CONTAINERS.

SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION

ENGINEERING CONTROLS: NO SPECIFIC CONTROLS NEEDED. GENERAL AND LOCAL EXHAUST RECOMMENDED.

RESPIRATORY PROTECTION: NONE REQUIRED IN ADEQUATELY VENTILATED AREAS. APPROPRIATE RESPIRATORY PROTECTION IS REQUIRED WHEN EXPOSURE TO AIRBORNE CONTAMINANTS MAY EXCEED ACCEPTABLE LIMITS. RESPIRATORS SHOULD BE SELECTED AND USED IN ACCORDANCE WITH OSHA, SUBPART I (29 CFR 1910.134)

EYE PROTECTION: SPLASH-PROOF GOGGLES OR CHEMICAL SAFETY GLASSES.

OTHER PROTECTIVE EQUIPMENT: LONG SLEEVED SHIRTS AND TROUSERS. EMERGENCY SHOWERS AND EYE WASH STATIONS SHOULD BE READILY ACCESSIBLE.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: >100⁰ C (212⁰ F)

SPECIFIC GRAVITY: 1.34

VAPOR PRESSURE: ND

MELTING POINT: ND

VAPOR DENSITY: >1

EVAPORATION RATE: <1

(AIR = 1)

(BUTYL ACETATE = 1)

SOLUBILITY IN WATER: SOLUBLE

COEFFICIENT of WATER/OIL DISTRIBUTION: ND

APPEARANCE AND ODOR: WHITISH LIQUID WITH SLIGHT ODOR.

ODOR THRESHOLD: NE

SECTION 10: STABILITY AND REACTIVITY

STABILITY: STABLE.

CONDITIONS TO AVOID: NOT APPLICABLE (MATERIAL IS STABLE).

INCOMPATIBILITY (MATERIAL TO AVOID): NONE KNOWN

HAZARDOUS DECOMPOSITION PRODUCTS: NONE

HAZARDOUS POLYMERIZATION (REACTIVITY): WILL NOT OCCUR.

SECTION 11: TOXICOLOGICAL INFORMATION

ACUTE TOXICITY EFFECTS:

INGESTION: ND

DERMAL: ND

INHALATION: ND

EYE IRRITATION: SLIGHT IRRITATION

SENSITIZATION: NA

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICITY EFFECTS:

AQUATIC TOXICITY, ND

BIODEGRADABILITY: NOT READILY BIODEGRADABLE

MOBILITY: ND

BIOACCUMULATION: ND

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHODS: INCINERATION IS PREFERRED. COMPLY WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS. CHEMICAL AND/OR BIOLOGICAL DEGRADATION IS FEASIBLE.



MATERIAL SAFETY DATA SHEET

PRODUCT NAME: XL 70 W PRIMER
PRODUCT CODE: PR70W

Page 4 of 4

SECTION 14: TRANSPORT INFORMATION

DOT PROPER SHIPPING NAME: RESIN SOLUTION, NOT REGULATED
HAZARD CLASS: IRRITANT.
UN NUMBER: NA
PACKING GROUP: NA
IMO SHIPPING DATA: RESIN SOLUTION, NOT REGULATED.
ICAO/IATA SHIPPING DATA: RESIN SOLUTION, NOT REGULATED.

SECTION 15: REGULATORY INFORMATION

TSCA (TOXIC SUBSTANCE CONTROL ACT): ALL COMPONENTS ARE LISTED IN THE TSCA CHEMICAL SUBSTANCE INVENTORY.
EU,EINECS: THE POLYMER CONTAINED WITHIN THIS PRODUCT IS EXEMPT FROM LISTING IN THE EUROPEAN INVENTORY. THE MONOMERS USED TO MANUFACTURE THE POLYMER ARE LISTED AS REQUIRED, AS ARE ALL OTHER COMPONENTS OF THIS PRODUCT
CANADIAN WHMIS CLASSIFICATION: D2(B)
CERCLA (COMPREHENSIVE RESPONSE COMPENSATION and LIABILITY ACT): ND
SARA TITLE III
SECTION 312 HAZARD CLASS: NA
SECTION 313 LISTED INGREDIENTS: ZINC OXIDE (1-5%).
CALIFORNIA PROPOSITION 65: The below list of compounds is known to the State of California to cause cancer, birth defects or other reproductive harm: NONE

SECTION 16: OTHER INFORMATION

HMIS RATING	HEALTH	1	FLAMMABILITY	1	REACTIVITY	0
--------------------	---------------	---	---------------------	---	-------------------	---

(NA= NOT APPLICABLE) (NE=NOT ESTABLISHED)
(ND= NOT DETERMINED)

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the accuracy of the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects, which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations and orders.